



GR2025 Brief Datasheet

Lithium Manganese Dioxide Coin Batteries

1 BASIC SPECIFICATION

Nominal Voltage(V)	3.0
Nominal Capacity(mAh) Continuous discharge with 7.5k\Omega to 2.0V cut-off, +23°C	150
Continuous standard load (kΩ)	7.5
Operating temperature (°C)	-20~ +60
Weight (g)	2.4


Note: Typical values relative to cells stored for three months at 23°C.


0.0-0.3 0.0-0.3 0.0-0.3 0.0-0.3 0.0-0.3 0.0-0.3

2 MAIN FEATURES

- ♦ Light Weight, High Voltage and High Energy Density.
- ♦ Excellent Stable Discharge Characteristics and outstanding Temperature Characteristics.
- ♦ Excellent Leakage Resistance and Excellent Long-term Reliability.

3 ELECTRICAL CHARACTERISTICS





4 WARNING!

- ♦ Do not recharge, short-circuit, disassemble, deform, heat or place the battery near a direct flame. Any of the above actions could cause it to ignite explode or become damaged.
- ♦ Keep this battery out of the reach of children.
- ♦ When storing the battery or throwing it away, be sure to cover it with tape.

Note: Any representations in this brochure concerning performance, are for informational purposes only and are not construed as warranties either expressed or implied, of future performance.