



| | | | | | |
|---------------------------------|---|----------------|----------------------------------|--|-----------|
| Cell(电芯): | LP782426 | Date code(喷码): | Inner controlling standard(内控标准) | | |
| Battery Specification (电池参数) | Min Capacity 最低容量 (mAh) (0.2C,25±3°C) *Single battery capacity (单体电池容量) | 380 | *PCM protection (保护板参数) | Overcurrent Detection(A) (过流值) | 2~6 |
| | Typical Capacity 典型容量 (mAh) (0.2C,25±3°C) *Single battery capacity (单体电池容量) | 420 | | Overcharge Detection Voltage(V) (过充保护电压) | 4.28±0.05 |
| | Nominal Voltage 标称电压 (V) | 3.7 | Ambient Conditions (工作环境) | Overdischarge Detection Voltage(V) (过放保护电压) | 2.3±0.1 |
| | Internal impedance 内阻 (≦) (mΩ,AC 1KHZ) | 250 | | Charge Temp.充电温度 (°C) | 0-45 |
| | | | Discharge Temp.放电温度 (°C) | -20-60 | |
| | | | Humidity(湿度) | 65±20% | |

Remark(备注):
 1. No scratch, distortion, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
 2. Rohs compliant(严格按照ROHS要求生产).

| | | | | | |
|----------|------------------|------------|-----------|-------------|---------|
| | | Draft: | Approved: | Revise No.: | E4-2009 |
| | | | Moyongdi | Projection: | |
| Title | LP782426+PCM-LD/ | | Holly | Page: | 1/1 |
| File NO. | A01612 | Draw Date: | Keyan | Scale: | 1 : 1 |
| | | | 09/10/20 | Unit: | mm |