



Cell(电芯):	2LP255455HA		Date code(喷码):		Inner controlling standard(内控标准)	
	Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C)	550	*PCM protection (保护板参数)	Overcurrent Detection(A) (过流值)	6.5-10.5	
	*Single battery capacity (单体电池容量)	600		Overcharge Detection Voltage(V) (过充保护电压)	4.3±0.05	
	Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C)	600	Overdischarge Detection Voltage(V) (过放保护电压)	2.4±0.1		
*Single battery capacity (单体电池容量)	600	Charge Temp. 充电温度 (°C)	0-45			
Nominal Voltage 标称电压 (V)	7.4	Discharge Temp. 放电温度 (°C)	-20-60			
Internal impedance 内阻 (≦) (mΩ, AC 1KHZ)	300	Humidity(湿度)	65±20%			

EEMB BATTERY Title: 2LP255455HA-PCM-LD File NO.: A02564		Draft: Approved: Moyongdi Projection:	
Draw Date: 09/12/04		Approved: Keyan Revision No.: E4-2009 Page: 1/1 Scale: 1 : 1.4 Unit: mm	

Remark(备注):
 1. No scratch, distortion, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
 2. Rohs compliant(严格按照ROHS要求生产).