


REV	MODIFICATIONS	DRAWN BY	CHECKED BY	DD/MM/YY
AA	Creation	JZ	***	09/04/10
BA	Tin plated	JZ	ToH	14/07/10
CA	gold plated - change of L	ToH	JZ	25/10/11
DA	marking added	ToH	JZ	27/10/11

-Camera checking



AVX6288-shape

CHARACTERISTICS

ITEMS	VALUE	TEST METHOD
Resistance of conductor	1460 Ohm/km maxi	-
Insulation resistance (Conductor to conductor)	10 MOhm.m mini	500 V DC
Dielectric test (Conductor to conductor)	1 minute	200 V AC
Temperature rating	-40°C to 105°C	-
Voltage rating	60 V AC maxi	-
Flame resistance	VW-1	UL758

COMPOSITION

COMPONENTS	UNITS	SPECIFICATIONS	ITEM
Conductor	Material	Plating (min. 0.3µm Ni/min. 0.05µm Au)	1
	Dimensions	0,30 x 0,05 mm	
Insulation	Material	Polyester+flame retardant adhesive insulation	2 3
	Dimensions	0,086 mm nominal	
Reinforcement	Material	Blue polyester	4 5
	Dimensions	0,180 mm nominal	

Ink jet marking on side itemized 2 and 3 : 196937/00	Position : centred
Ink : Ink Jet black	Height : 2,5 mm
Position : 60mm from the cable end with the reinforcement (both sides)	

UNLESS OTHERWISE SPECIFIED
DIMENSIONS : MM ANGLES : °

AXON' KABEL GmbH
71229 LEONBERG
TEL. : +49 7152 97992-0
FAX : +49 7152 97882-86
www.axon-cable.com

CUSTOMER N° 196937/00	TITLE
FILE N° SJ10205D.dwg	FFC0.50D55/1470S4.0-4.0-08.0-08.0FAU/AU M N spe tol
SIZE A4	AXON' GmbH N°
SCALE : N/D.	SJ10205
REV. D	A
Prod.	Doc.
SHEET 1 of 1	

This drawing is the property of Axon', and is issued on the condition that it is not copied or disclosed to any third party without prior written consent from Axon'Cable