


REV	MODIFICATIONS	DRAWN BY	CHECKED BY	DD /MM/YY
AA	Creation	NT	JZ	21/12/09
BA	Gold	JZ	***	14/04/10
CA	modification of L	ToH	JZ	27/04/10
DA	modification+marking added	ToH	JZ	05/08/10
EA	modification	ToH	***	23/08/10




- camera checking

CHARACTERISTICS

ITEMS	VALUE	TEST METHOD
Resistance of conductor	730 Ohm/km max	-
Insulation resistance (conductor to conductor)	10 MOhm.m min	500 V DC
Dielectric test	200 V AC	1 minute
Temperature rating	-40°C to 105°C	UL style 20706
Voltage rating	60 V AC max	UL758
Flame resistance	VW-1	UL758

COMPOSITION

COMPONENTS	UNITS	SPECIFICATIONS	ITEM
Conductor	Material	Golden contacts (0,3µm Ni/0,05µm Au min)	1
	Dimensions	MM 0,30 x 0,10 mm	
Insulation	Material	Polyester+flame retardant adhesive insulation	2 3
	Dimensions	MM 0,086 mm nominal	
Reinforcement tape	Material	Blue polyester	4 5
	Dimensions	MM 0,155 mm nominal	
Ink jet marking on side itemized 3 : 161.554/00			
Ink : Ink jet black			



AVX6288—shape

UNLESS OTHERWISE SPECIFIED
DIMENSIONS : MM ANGLES : °

CUSTOMER N°
161.554/00
FILE N°
SU09769E.dwg

AXON KABEL GmbH
KABEL & VERBINDUNGSSYSTEME
71229 LEONBERG
TEL : +49 7152 97992-0
FAX : +49 7152 97692-66
www.axon-sidac.com

TITLE
FFCO.50A60/005354.0-4.0-08.0-08.0SAKK/AU M N spe tol

AXON GmbH N°
SU09769

REV E A
Prod. Doc.
SHEET 1 of 1

This drawing is the property of Axon', and is issued on the condition that it is not copied or disclosed to any third party without prior written consent from Axon'Cable