


REV	MODIFICATIONS	DRAWN BY	CHECKED BY	DD /MM /YY
AA	Creation	NT	JZ	21/12/09
BA	Gold	JZ	***	14/04/10
CA	modification of L	ToH	JZ	27/04/10
DA	modification	ToH	JZ	05/08/10
DB	modi pos of marking	ToH	***	23/08/10




— camera checking

CHARACTERISTICS

ITEMS	VALUE	TEST METHOD
Resistance of conductor	730 Ohm/km max	—
Insulation resistance (conductor to conductor)	10 MOhm.m min	500 V DC
Dielectric test	200 V AC	1 minute
Temperature rating	-40°C to 105°C	
Voltage rating	60 V AC max	UL style 20706
Flame resistance	VW-1	UL758

COMPOSITION

COMPONENTS	UNITS	SPECIFICATIONS	ITEM
Conductor	—	Golden contacts (0,3µm Ni/0,05µm Au min)	1
Insulation	Dimensions	0,30 x 0,10 mm	2 3
	Material	Polyester+flame retardant adhesive	
Reinforcement tape	Dimensions	0,086 mm nominal	4 5
	Material	Blue polyester	



AVX6288—shape

UNLESS OTHERWISE SPECIFIED
DIMENSIONS : MM ANGLES : °

FILE NO: 4.0/2mm* 2001/74-LM
CUSTOMER N°: 161.553/00
FILE N°: SJ09771D.dwg

AXON KABEL GmbH
KABEL & VERBINDUNGSSYSTEME
AXON KABEL GmbH
71229 LEONBERG
TEL : +49 7152 97992-0
FAX : +49 7152 97692-86
www.axon-sidac.com

TITLE: FFC0 50D08/0120S4.0-4.0-08.0-08.0SAKK/AU M N spe tol

AXON GmbH N°: SJ09771

REV D Prod. B
REV D Prod. B
SHEET 1 of 1

This drawing is the property of Axon', and is issued on the condition that it is not copied or disclosed to any third party without prior written consent from Axon'Cable