



Recommended PCB Layout

NOTES:

1. Insulation : High Temperature Plastic UL 94-0
Color Red
2. Contact : Phosphor Bronze
3. Plating : Matte Tin plated over Nickel
4. Contacts type: SMT Type
5. Packing: Reel packing

A-32-xx M-130x

latch option:
0= without latch
L= with latch

A = 1.27x No. of Spaces

B = A + 5.87

C = A + 1.80

D = A + 3.27

*Available in 4~26 circuits

RoHS compliant

Scale	1:1						Date	Name	Customer-No.
TOLERANCE						Drawn	05.08.2009	Dean	
.X	±0.30					Approved	05.08.2009	Hellwig	ASSMANN WSW-No.
.XX	±0.20								A-32-xx M-130x
.XXX	±0.10								Drawing-No.
DIM	TOL							ASS 3633 CO rev01	
X.°	±1°	①	Drawn	05.08.2009	Dean			Replace	SHEET
X.X°	±X°	Id.	Modification	Date	Name			1/2	
Angle	TOL								

1 2 3 4 5 6 7

A B C D E F

NOTES:

1. 10 sprocket hole pitch cumulative tolerance ±0.20.
2. Carrier camber not to exceed 1 mm in 100 mm.
3. Material : Transparent Anti-static Polystyrene.
4. All dimensions meet EIA-481-3 requirements
5. Thickness : 0.40±0.05 mm.
6. Packing length per 22" reel : 30.6 Meters
7. Component load per 13" reel: 600 pcs

Circuits	Dimension					Packing (Reel/Carton)
	E	F	W1	W2	W3	
4-8	24.0	-	24.5	30.5	24.5	9
10-12	32.0	28.40	32.5	38.5	32.5	7
14-22	44.0	40.40	44.5	50.5	44.5	5
24-26	56.0	52.40	56.5	62.5	56.5	4

WIDTH: 24 mm Carrier

WIDTH: 32,44,56 mm Carrier

RoHS compliant

Scale	Free				Date	Name	Customer-No.
TOLERANCE					Drawn	05.08.2009	Dean
.X	±X				Approved	05.08.2009	Hellwig
.XX	±X						
.XXX	±X						
DIM	TOL						Drawing-No.
X.°	±1°						ASSMANN WSW-No. A-32-xx M-130x
X.X°	±X°	①	Drawn	05.08.2009	Dean		
Angle	TOL	Id.	Modification	Date	Name		Replace

ASS 3633 CO rev01

SHEET 2/2

1 2 3 4 5 6 7

H

svxxxx