


REV	MODIFICATIONS	DRAWN BY	CHECKED BY	DD/MM/YY
AA	Creation	JZ	***	09/04/10
BA	tin plated	JZ	ToH	14/07/10
CA	gold plated – change of L	ToH	JZ	25/10/11
DA	marking added	ToH	JZ	27/10/11

Camera checking



AVX6288 – shape

CHARACTERISTICS

ITEMS	VALUE	TEST METHOD
Resistance of conductor	1460 Ohm/km maxi	–
Insulation resistance (Conductor to conductor)	10 Mohm.m mini	500 V DC
Dielectric test (Conductor to conductor)	1 minute	200 V AC
Temperature rating	–40°C to 105°C	–
Voltage rating	60 V AC maxi	–
Flame resistance	VW-1	UL758

COMPOSITION

COMPONENTS	UNITS	SPECIFICATIONS	ITEM
Conductor	–	Plating (min. 0,3µm Ni/min. 0,05µm Au)	1
Insulation	Dimensions	0,30 x 0,05 mm	2 3
	Material	Polyester+flame retardant adhesive insulation	
Reinforcement tape	Dimensions	0,086 mm nominal	4 5
	Material	Blue polyester	
	Dimensions	0,180 mm nominal	

Ink jet marking on side itemized 2 and 3 : 196857/00
 Ink : Ink Jet black Height : 2,5 mm Position : centred
 Position : 60mm from the cable end with the reinforcement (both sides)

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS : MM ANGLES : °

axxon'
 KABEL & VERBINDUNGSSYSTEME
 AXON' KABEL GmbH
 71229 LEONBERG
 TEL. : +49 7152 97992-0
 FAX : +49 7152 97882-86
 www.axon-cable.com

CUSTOMER N° 196857/00	TITLE	REV. D	A
FILE N° SJ10204D.dwg	FFC0.50D55/2140S4.0-4.0-08-0-08.0FAU/AU M N spe tol	Prod.	Doc.
SIZE A4 SCALE : N/D.	AXON' GmbH N° SJ10204	SHEET 1 of 1	