



P.C.B Layout

NOTES:

MATERIAL

- 1. Insulator: PA6T+30G.F (UL94V-0) Black
- 2. Contact: Brass
- 3. Contact Plating : 1 u" Au over 50u" Ni

ELECTRICAL

- 1. Current Rating : 3.0Amps/contact max
- 2. Withstand Voltage : 1000V AC/minute
- 3. Contact Resistance : 20mΩ/contact max
- 4. Insulation Resistance: 1000MΩ min at Voltage=100V

ENVIRONMENTAL

- 1. Operation Temperature: -55°C to +105°C
- 2. Soldering Temperature: +260°C max, 10s
- 3. Mechanical life cycle: min.200

PACKING: Tube+Cap

RoHS compliant
Unit:mm

Scale	Free						Date	Name	Customer-No.
TOLERANCE						Drawn	21.02.2013	Amy	
X.X	±0.40					Approved	21.02.2013	Amy	ASSMANN WSW-No.
X.XX	±0.25								ADB-254-xx-ST2
X.XXX	±0.15								Drawing-No.
DIM	TOL					ASSMANN WSW components		ASS 5210 CO	
X°	±3°	①	Drawn	21.02.2013	Amy			Replace	rev00
Angle	TOL	Id.	Modification	Date	Name				SHEET