



Model: LP402535		Overcharge Detection Voltage(V) 过充保护电压(V)	4.28±0.05
Min. Capacity 最低容量(mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)		Overdischarge Detection Voltage(V) 过放保护电压(V)	3.0±0.1
300		Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 0.5 (A)	constant (A) 持续 0.2 (A)
Typical Capacity 典型容量(mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)		Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 (A)	
320		constant (A) 持续 (A)	
Nominal Voltage 标称电压(V)		Battery protection Related Value: (相关的电池保护值)	
3.7			
Internal impedance 内阻(≅) (mΩ, AC 1KHz)			
250			
Charge Temp. 充电温度(°C)			
0~45			
Discharge Temp. 放电温度(°C)			
-20~60			
Humidity(湿度)			
65±20%			

		Drawn: Sophie		Revise No.: E4-2009	
		Checked 1: Elvira		Projection:	
Title		Checked 2:		Page: 1/1	
File NO. LP402535-PCM-LD/A09206		Approved:		Scale: 1.3:1	
		Draw Date: 2014/02/14		Unit: mm	

Remark(备注):  
 1. No scratch, distortion, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).  
 2. Rols compliant(严格按照ROHS要求生产).