

X Scale : 5:1  
Y Scale : 1:5


Index	Modifications	Drawn.	Check.	Date
A	Creation	JZ	***	30/04/2014

## CHARACTERISTICS

ITEMS	VALUE	TEST METHOD
Resistance of conductor	730 Ohm/km max	23°C
Insulation resistance (conductor to conductor)	10 MOhm.m min	200 V DC
Dielectric test (conductor to conductor)	1 minute	200 V AC
Temperature rating	105 °C max	UL20706
Voltage rating	60 V AC max	UL20706
Flame resistance	VW - 1	UL 758

## DIMENSIONS

ITEMS	SPECIFICATIONS
Number of conductors	26
Pitch	0.50 ± 0.05
Span	12.50 ± 0.10
Total width	13.50 ± 0.06
Margin	M 0.50 + 0.15 / - 0.096
Strip length	S1 4.0 ± 0.8
Strip length	S2 4.0 ± 0.8
End thickness	T1 0.30 ± 0.05
End thickness	T2 0.30 ± 0.05
Insulated length	L 342 ± 5
Reinforcement length	F1 6.0 ± 2.0
Reinforcement length	F2 6.0 ± 2.0
Strips differences S-S'	0.3 max



Scale : 5:1

## COMPOSITION

ITEM	COMPONENTS	MATERIAL	DIMENSIONS (nominal in mm)
1	Conductor	Tin plated copper (2µm min)	0.3 x 0.1
2	Insulation	Polyester (White)	0.073
3	Insulation	Polyester (White)	0.073
4	Reinforcement tape	Polyester (Blue)	0.155
5	Reinforcement tape	Polyester (Blue)	0.155

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS



**AXON KABEL GmbH**  
POSTFACH 1131 D - 71209 LEONBERG  
HERTICHSTR. 43D - 71229 LEONBERG  
EMAIL: sales@axon-cable.de  
TEL: +49 7152-97992-0  
www.axon-cable.com

Customer

CAD Number  
010793.dwg

010793

N. AXON'

FFC0.50A26/0342B4.0-4.0-06.0-06.0SAKK

