



X Scale : 5:1
Y Scale : 1:5

Index	Modifications	Drawn.	Check.	Date
A	Creation	JZ	ToH	21/01/2015



CHARACTERISTICS

ITEMS	VALUE	TEST METHOD
Resistance of conductor	1460 Ohm/km max	23°C
Insulation resistance (conductor to conductor)	10 MOhm.m min	200 V DC
Dielectric test (conductor to conductor)	1 minute	200 V AC
Temperature rating	105 °C max	UL 20706
Voltage rating	60 V AC max	UL 20706
Flame resistance	VW - 1	UL 758

DIMENSIONS

ITEMS	SPECIFICATIONS
Number of conductors	6
Pitch	P 0.50 ± 0.05
Span	E 2.50 ± 0.10
Total width	W 3.50 ± 0.06
Margin	M 0.50 +0.15/-0.096
Strip length	S1 4.0 ± 0.5
Strip length	S2 4.0 ± 0.5
End thickness	T1 0.30 ± 0.05
End thickness	T2 0.30 ± 0.05
Insulated length	L 370 ± 5
Reinforcement length	F1 6.0 ± 1.5
Reinforcement length	F2 6.0 ± 1.5
Strips differences S-S'	0.3 max

UNLESS OTHERWISE SPECIFIED DIMENSIONS: mm / ANCHORS: °



AXON KABEL GmbH
POSTFACH 1131 D - 71209 LEONBERG
HERTICHSTR. 43D - 71229 LEONBERG
EMAIL: sales@axon-cable.de
TEL: +49 7152-97992-0
www.axon-cable.com


SJ15042A

COMPOSITION

ITEM	COMPONENTS	MATERIAL	DIMENSIONS (nominal in mm)
1	Conductor	Tin plated copper (2µm min)	0.3 x 0.05
2	Insulation	Polyester (White)	0.073
3	Insulation	Polyester (White)	0.073
4	Reinforcement tape	Polyester (Blue)	0.18
5	Reinforcement tape	Polyester (Blue)	0.18

Customer
Ineltro
CAD Number
SJ15042A.dwg

N. AXON'



FFCO.50DD06/0370B4.0-4.0-06.0-06.0FAJJ spe 101