




















Product Image	Product Name	Capacitance (F)	Rated Voltage (V)	Maximum Operating Voltage (V)	ESR, DC (mohm)	ESR, AC @ 1kHz (mohm)	Ic (mA)	Max. peak current (A), 1 sec	Max. continuous current (A)	Weight (kg)	Energy Available (Wh)	Emax (Wh/kg)	Emax (Wh/L)	Pmax (W/kg)	Pmax (Wh/L)	Terminal
	PC10	10	2.5	2.5	180	130	0.04	4.5	2.5	0.0063	0.009	1.38		1,900		Lead
	BCAP0005 P270	5	2.7	2.85	200	110	0.015	3.4	1.6	0.0022	0.005	2.3		7,500		Lead
	BCAP0010 P270	10	2.7	2.85	80	60	0.03	7.5	3.5	0.004	0.01	2.53		7,550		Lead
	BCAP0025 P270	25	2.7	2.85	42	30	0.045	16.5	5	0.007	0.025	3.62		8,678		Radial lead
	BCAP0050 P270	50	2.7	2.85	20	15	0.075	33.8	5	0.014	0.051	3.62		8,678		Radial lead
	BCAP0100 P270	100	2.7	2.85	15	9	0.26	54	8.2	0.025	0.1	4.05		8,100		Snap in
	BCAP0150 P270	150	2.7	2.85	14	8	0.5	65.3	5	0.035	0.15	4.34		6,509		Snap in
	BCAP0310 P270 T08	310	2.7	2.85	2.2	1.1	0.45	248	30	0.062	0.31	5.06		26,700		Radial
	BCAP0350 E270 T09	350	2.7	2.85	3.2	1.6	0.3	222	25	0.063	0.354	5.62		18,300		Radial
	BCAP0650 P270 T04	650	2.7	2.7	0.8	0.6	1.5	577	62	0.2	0.658	3.29		15,100		Threaded
	BCAP0650 P270 T05	650	2.7	2.7	0.8	0.6	1.5	577	62	0.2	0.658	3.29		15,100		Weldable
	BCAP1200 P270 T04	1200	2.7	2.85	0.58	0.44	2.7	955	81	0.3	1.215	4.05		13,800		Threaded
	BCAP1200 P270 T05	1200	2.7	2.85	0.58	0.44	2.7	955	81	0.3	1.215	4.05		13,800		Weldable
	BCAP1500 P270 T04	1500	2.7	2.85	0.47	0.35	3.0	1,187	97	0.32	1.519	4.75		16,200		Threaded
	BCAP1500 P270 T05	1500	2.7	2.85	0.47	0.35	3.0	1,187	97	0.32	1.519	4.75		16,200		Weldable
	BCAP2000 P270 T04	2000	2.7	2.85	0.35	0.26	4.2	1,588	123	0.4	2.025	5.06		17,500		Threaded
	BCAP2000 P270 T05	2000	2.7	2.85	0.35	0.26	4.2	1,588	123	0.4	2.025	5.06		17,500		Weldable
	BCAP3000 P270 T04	3000	2.7	2.85	0.29	0.24	5.2	2,165	147	0.55	3.038	5.52		13,800		Threaded
	BCAP3000 P270 T05	3000	2.7	2.85	0.29	0.24	5.2	2,165	147	0.55	3.038	5.52		13,800		Weldable

Product Image	Product Name	Capacitance (F)	Rated Voltage (V)	Maximum Operating Voltage (V)	ESR, DC (mohm)	ESR 1kHz (mohm)	Ic (mA)	Max. peak current (A), 1 sec	Max. continuous current (A)	Weight (kg)	Energy Available (Wh)	E <sub>max</sub> (Wh/kg)	E <sub>max</sub> (Wh/L)	P <sub>max</sub> (W/kg)	P <sub>max</sub> (Wh/L)	Balancing	Thermal Monitoring	Protection Level
	BPAK0052 P015 B01	52	15	15	14.5	8	1	80	20	0.566	1.84	3.25		14,000		Active	N/A	-
	BPAK0058 E015 B01	58	15	15	19	10	1	80	20	0.566	2.06	3.63		11,200		Active	N/A	-
	BPAK0058 E015 B02	58	15	15	19	10	50	80	20	0.566	2.06	3.63		11,200		Passive	N/A	-
	BMOD0052 P015 B01	52	15	15	14.5	8	1	80	20	0.68	1.63	2.39		10,300		Active	N/A	-
	BMOD0058 E015 B01	58	15	15	19	10	1	80	20	0.68	1.82	2.67		8,200		Active	N/A	-
	BMOD0058 E015 B02	58	15	15	19	10	50	80	20	0.68	1.82	2.67		8,200		Passive	N/A	-
*	BMOD0058 E016 B02	58	16.2	16.2	22	10		206	20	0.55	2							
	BMOD0110 P016 B01	110	16.2	16.2	5.6	4	1.5	-	30	2.9	4	1.49		6,000		VMS	Y	IP65
	BMOD0250 P016 B01	250	16.2	16.2	4.1	3.3	3	2,025	115	4.45	9	2.05		4,400		VMS	Y	IP65
	BMOD0500 P016 B01	500	16.2	16.2	2.4	1.7	5.2	4,050	150	5.75	18	3.17		6,700		VMS	Y	IP65
	BMOD0500 P016 B02	500	16.2	16.2	3	1.7	150	4,050	150	5.75	18	3.17		6,700		Passive	Y	IP65
	BMOD0083 P048 B01	80	48.6	48.6	12.3	9.8	3	2,010	115	11	27	2.91		6,200		VMS	Y	IP65
	BMOD0110 P048 B01	110	48.6	48.6				2,673			36							
	BMOD0165 P048 B01	165	48.6	48.6	7.1	5.2	5.2	4,000	150	13.5	54	3.81		7,900		VMS	Y	IP65
	BMOD0094 P075 B02	94	75	86	12.5	-	5.2	3,525	50	25	73	3.98		6,800		Passive	Y	IP54 SAEJ2380
	BMOD0063 P125 B14 BMOD0063 P125 B24	63	125	130	18	14.0	5.2	3,930	150	58	137	2.53		5,200		VMS	Y	IP65

\* Available Q4 2009