



Contact Point

NOTES:

1. Insulation: Glass Filled PBT, UL94V-0, Color Black/Red/Blue
2. Contact : Phosphor Bronze
3. Current Rating: 3A Max
4. Dielectric Voltage: 1000V rms / 1 minute
5. Insulation Resistance: 1000M ohm Min.
6. Contact Resistance: 30m ohm Max.
7. Operating and Storage Temperature: -40°C ~ +105°C

AKSCT/x x

Contact Plating:
G: Gold Flash
Z: Tinned

Insulation color: 2
BLACK: Black
BLUE: Blue
RED: Red



RoHS compliant

Scale	Free						Date	Name	Customer-No.	
TOLERANCE							Drawn	10.04.2002	Hellwig	
.X	±0.38						Approved	21.11.2012	Amy	ASSMANN WSW-No. AKSCT/G X AKSCT/Z X
.XX	±0.25									
.XXX	±0.13	③	Update		21.11.2012	Amy				
DIM	TOL	②	Update		27.07.2009	Rale	ASSMANN WSW components			
X.°	±1°									
Angle	TOL	①	Drawn		10.04.2002	Hellwig	ASS 0591 CO		rev03	
UNIT	mm	Id.	Modification		Date	Name	Replace		SHEET	



ASS 0591 CO

rev03

Replace

SHEET