

	1	2	3	4	5	6	7																																																																									
A	<p>①</p>							A																																																																								
B								B																																																																								
C	<p><b>NOTES:</b></p> <p><b>MATERIAL</b></p> <p>1. Insulator Material: PBT+30%GF(UL94V-0), Black</p> <p>2. Contact Material : Brass</p> <p>3. Contact Plating : 20u" Au over Ni</p>							C																																																																								
D	<p><b>ELECTRICAL</b></p> <p>1. Current Rating : 3.0AMP/contact max.</p> <p>2. Withstand Voltage : 1000V AC/minute</p> <p>3. Contact Resistance : 20mΩ max</p> <p>4. Insulation Resistance: 1000MΩ min</p>							D																																																																								
E	<p><b>ENVIRONMENTAL</b></p> <p>1. Operation Temperature: -55°C to +105°C</p> <p>2. Packing: Tray</p>							E																																																																								
F	<p><b>P.C.B LAYOUT</b></p>							F																																																																								
G	<p><b>RoHS compliant</b></p> <table border="1"> <thead> <tr> <th>Scale</th> <th>1:1</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td><b>TOLERANCE</b></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.X</td> <td>±0.40</td> <td></td> <td></td> <td>Drawn</td> <td>18.05.2015</td> <td>Ray</td> <td></td> </tr> <tr> <td>X.XX</td> <td>±0.25</td> <td></td> <td></td> <td>Approved</td> <td>18.05.2015</td> <td>Ray</td> <td></td> </tr> <tr> <td>X.XXX</td> <td>±0.15</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>DIM</b></td> <td><b>TOI</b></td> <td></td> <td></td> <td>①</td> <td>Update drawing</td> <td>18.05.2015</td> <td>Ray</td> </tr> <tr> <td><b>Angle</b></td> <td>±3°</td> <td></td> <td></td> <td>②</td> <td>Drawn</td> <td>26.10.2010</td> <td>Ray</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							Scale	1:1							<b>TOLERANCE</b>								X.X	±0.40			Drawn	18.05.2015	Ray		X.XX	±0.25			Approved	18.05.2015	Ray		X.XXX	±0.15							<b>DIM</b>	<b>TOI</b>			①	Update drawing	18.05.2015	Ray	<b>Angle</b>	±3°			②	Drawn	26.10.2010	Ray																	G
Scale	1:1																																																																															
<b>TOLERANCE</b>																																																																																
X.X	±0.40			Drawn	18.05.2015	Ray																																																																										
X.XX	±0.25			Approved	18.05.2015	Ray																																																																										
X.XXX	±0.15																																																																															
<b>DIM</b>	<b>TOI</b>			①	Update drawing	18.05.2015	Ray																																																																									
<b>Angle</b>	±3°			②	Drawn	26.10.2010	Ray																																																																									
H	<table border="1"> <thead> <tr> <th>Id.</th> <th>Modification</th> <th>Date</th> <th>Name</th> <th>Customer-No.</th> <th>ASSMANN WSW-No.</th> <th>Drawing-No.</th> <th>Replace</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>A-BL_254-DG-GXXD-20</td> <td>ASS 4310 CO</td> <td>rev01</td> </tr> </tbody> </table>							Id.	Modification	Date	Name	Customer-No.	ASSMANN WSW-No.	Drawing-No.	Replace						A-BL_254-DG-GXXD-20	ASS 4310 CO	rev01	H																																																								
Id.	Modification	Date	Name	Customer-No.	ASSMANN WSW-No.	Drawing-No.	Replace																																																																									
					A-BL_254-DG-GXXD-20	ASS 4310 CO	rev01																																																																									
	1	2	3	4	5	6	7	S/027 S/0365																																																																								