Signature	Revision History	Date	Rev.
LIBRA	For Bulk Production	June30,2011	01

RoHS Compliant

USB A TYPE MALE

MINI USB 5P B TYPE MALE



NOTES:

1.CABLE: UL 2725 28AWG(7/0.12BC)*1P+28AWG(7/0.12BC)*2C+D28AWG(7/0.12BC)
+AL/MY+B(65% COVERAGE ALM) OD=4.2±0.20mm JACKET COLOR: BLACK
CABLE MUST PRINT: E****** AWM STYLE 2725 80℃ 30V VW-1

2.CONNECTOR:
P1 : USB A/M, SOLDER, WHITE INSULATION, 3u GOLD PLATED CONTACTS, NICKEL PLATED SHELL
P2 : MINI USB 5P B/M, SOLDER, BLACK INSULATION, 3u GOLD PLATED CONTACTS, NICKEL PLATED SHELL

3.HOOD: MOLDED TYPE,PVC 45P,COLOR:BLACK.

4.ELECTRICLE TEST:
(1)100% OPEN SHORT & MIS WIRE TEST.
(2)CONTACT RESISTANCE 2 ohm Max .
(3)INSULATION RESISTANCE 10M ohm Min .
(4)HI-POT TEST:DC 300V/10ms



Cross Section:



A-A

	Date	Name
Drawn by	June30,2011	Libra
Checked by		
Approved by		

ASSMANN
Electronic GmbH

STxxxxx

Part No.

AK-300108-010-S

EAN:4016032282891

Title

USB A/M - MINI USB 5P B/M CABLE

Scale	N/A	Sheet
Unit	MM	1/2

Signature	Revision History	Date	Rev.
LIBRA	For Bulk Production	June30,2011	01

Package Details

RoHS Compliant

Single Cable

P/N	Cable Length	Rolling Size (Single Cable)	Polybag Type (Single Cable)	Bag Size (Single Cable)	Article Weight (Single Cable)
AK-300108-010-S	1m	160mm max.	Ordinary Polybag (Heat Sealed)	180*100*0.05mm	0.034kg

Inner Packing Unit

P/N	Cable Length	Quantity (Inner Packing Unit)	Type (Inner Packing Unit)	Size (Inner Packing Unit)	Weight (Inner Packing Unit)
AK-300108-010-S	1m	10 pcs	Polybag (Heat Sealed)	280*230*0.05mm	0.344kg

CARTON DETAILS

P/N	Cable Length	Quantity (Carton)	Measurement (Carton)	N.W. (Carton)	G.W. (Carton)
AK-300108-010-S	1m	300pcs	38*30*31cm	9.6kg	11.0kg



* "ROTTERDAM" is for Sea Freight shipment
* "COLOGNE" is for Air Freight shipment
* "LUDENSCHEID" is for Fedex or UPS shipment

Single Cable



Inner Packing Unit



	Date	Name
Drawn by	June30,2011	Libra
Checked by		
Approved by		

ASSMANN Electronic GmbH

STxxxxx

Part No.

AK-300108-010-S

EAN:4016032282891

Title

USB A/M - MINI USB 4P B/M CABLE

Scale	N/A	Sheet
Unit	MM	2/2