


●● **GL865-DUAL V3**

GSM | GPRS Embedded



Product Description

The V3 variant of the GL865-DUAL is based on the latest chipset technology, designed to protect your design investments as a low-cost, long-term availability solution. It is recommended for any new cost-sensitive designs requiring 2G GSM/GPRS coverage and long term application cost stability, such as security alarms, automated meter reading, and POS terminals.

The new generation GL865-DUAL V3 operates with 1.8 V GPIOs versus its predecessor's 2.8 V, minimizing power consumption and making it even more ideally suited for battery powered and wearable device applications.

Embedded Python Script Interpreter in the GL865-DUAL V3 makes it possible to run the customer's application inside the module making it a complete SMT platform for m2m solutions.

An optional factory mounted m2mAIR embedded SIM-chip is available.

Key Benefits

- Easy upgrade path for applications currently using other modules of the GL865 series
- Recommended platform for applications requiring ultra low power consumption
- PYTHON Script Interpreter - customers can run their Python applications directly inside the module
- Long-term availability solution ideal for cost-sensitive applications
- Premium FOTA Management - Easy firmware update by transmitting only a small delta file

Family Concept

The Telit GL865 series features a compact LCC castellation (VQFN for the GL865-DUAL-V3) packaging that offers the option for manual soldering and removal, making this product suitable for low-volume niche applications. Versions are available having different supported bands: GL865-DUAL and GL865-QUAD.

Telit m2mLOCATE

m2mLOCATE is a Telit cloud-based service that provides a device's position based on observed cellular Cell-IDs. Accessing a database of over 40 million cell-IDs globally, m2mLOCATE can provide a position for every use-case including indoors/underground, outdoors, and boundary situations.



m2mAIR Ready

This product is capable of supporting the extensive suite of m2mAIR value-added services and connectivity you can use to enhance your application and boost your competitive advantage.

Find more information on www.m2mair.com

AVAILABLE FOR

- EMEA
- North America
- Latin America
- APAC
- Korea
- Australia

Combine your Cellular module with

- Short Range modules 
- GNSS modules 

www.telit.com

Complete, Ready to Use Access to the Internet of Things



Telit Modules + m2mAIR Value-Added Services including Connectivity

m2mAIR
by Telit m2m experts

www.m2mAIR.com

ONE STOP.
ONE SHOP. NOW, INNOVATE!



●● GL865-DUAL V3

Product features

- VQFN form factor
- Dual-band EGSM 900 / 1800 MHz
- GSM/GPRS protocol stack 3GPP Release 4 compliant
- Control via AT commands according to 3GPP TS 27.005, 27.007 and Telit custom AT commands
- Serial port multiplexer 3GPP TS 27.010
- SIM access profile
- SIM application toolkit 3GPP TS 51.014
- DARP/SAIC support
- SMS support
- SMS over GPRS
- Telephony, emergency call
- Half rate, full rate, enhanced full rate and adaptive multi rate voice codecs (HR, FR, EFR, AMR)
- Superior echo cancellation & noise reduction
- Multiple Audio profiles pre-programmed and fully configurable by mean AT commands
- Embedded DTMF decoder
- SIM phonebook
- Fixed dialing number (FDN)
- Real-time clock
- Alarm management
- Network LED support
- IRA, GSM, 8859-1 and UCS2 character set
- Jamming detection
- Embedded TCP/IP stack, including TCP, IP, UDP, SMTP, ICMP and FTP protocols
- PFM (Premium FOTA Management) Over-The-Air Update service
- Remote AT commands
- Event monitor
- Telit's EASY features
EASY SCAN® automatic scan over GSM frequencies (also without SIM card)

Data

GPRS

- GPRS class 10
- Mobile station class B
- Coding scheme 1 to 4
- PBCCH support
- GERAN Feature Package 1 support (NACC, Extended TBF)

CSD

Environmental

- Dimensions: 24.4 x 24.4 x 2.6 mm
- Weight: 2.8 grams
- Extended temperature range
 - 40°C to +85°C (operational)
 - 40°C to +85°C (storage temperature)

Interfaces

- 8 I/O ports maximum (1.8 V logic level)
- Analog Audio (balanced), digital Audio
- 2 A/D plus 1 D/A converter
- Buzzer output
- ITU-T V.24 serial link through CMOS UART:
 - Baud rate from 300 to 115,200 bps
 - Autobauding up to 115,200 bps

Approvals

- Fully type approved conforming R&TTE directive
- CE, GCF

Electrical & Sensitivity

- Output power
 - Class 4 (2W) @ 900 MHz
 - Class 1 (1W) @ 1800 MHz
- Supply voltage range: 3.2 - 4.5 VDC (3.8 V DC recommended)
- Power consumption (typical values)
 - Power off: 2 uA (typical)
 - Idle (registered, power saving): 0.9 mA DRX=9
 - Dedicated mode: 200 mA @ max power level
 - GPRS cl.10: 330 mA @ max power level

Sensitivity:

- 108 dBm (typ.) @ 900 MHz
- 107 dBm (typ.) @ 1800 MHz

Software

Python* application resources

- Python* script interpreter (module takes the application code directly in the Python* language)
- Memory: 800 kB of NV memory for the user scripts and 1 MB RAM for the Python* engine usage



Join the Telit Technical Forum

For a quicker and more rewarding integration experience join the Telit Technical Forum. There you can browse the first open forum covering all m2m topics, get direct support by region (EMEA, North America, Latin America, APAC), take part in this quickly growing m2m community and exchange experiences.