

ZINC19 4U C236



SCALABLE RACKMOUNT SYSTEM FOR CHALLENGING AND NOISE SENSITIVE ENVIRONMENTS

- ▶ industrial grade for challenging environments – robust, reliable and sustainable
- ▶ high processing capability with Intel® 6th Gen Core™ i3/i5/i7 or XEON® E3
- ▶ modular concept allows easy customization
- ▶ low noise design

ZINC19 4U C236

Kontron's ZINC Systems are designed for demanding conditions and sophisticated industrial applications handling big amounts of data and to satisfy high requirements in computing and GPU power. The ZINC portfolio is available with Intel® Core™ i3/i5/i7 or XEON® E3 processors and up to 64 GByte DDR4 RAM. A high degree of customization is facilitated through features like removable drives,

various expansion cards and the availability of heights 2U as well as 4U.

Superior reliability, scalability, extended operational performance and tool-free maintenance contribute towards maximization of ROI while at the same time minimizing service and maintenance costs.

▶ TECHNICAL INFORMATION

SYSTEM	ZINC19 4U C236
DIMENSION	177 x 482 x 472 mm (4U x 19" x 18,58")
WEIGHT	Approx. 20 kg
PROCESSOR	Intel® XEON® E3-1200 v5, E3-1225 v5, E3-1275 v5, Intel® Core™ i7/i5/i3 6th generation, i3-6100TE, i5-6500TE, i7-6700
RAM	DDR4 2133 SDRAM (UDIMM) ECC (XEON® & i3 only) / Non-ECC 16/32/64 GByte
FRONT I/O	2x USB 3.0
REAR I/O	4x USB 3.0, 4x USB 2.0, 2x LAN, 1x RS232, Audio, 1x DVI-D, 2x DP
INTERNAL DRIVES*	2.5" SATA SSD/HDD (128 GByte/256 GByte/1 TByte), 3.5" SATA HDD (2 TByte/4 TByte/6 TByte)
REMOVABLE DRIVES*	DVD R/W 2x 2.5" SSD/HDD removable (128 GByte/256 GByte/1 TByte) 1x 3.5" HDD removable (2 TByte/4 TByte/6 TByte) 3x 3.5" HDD removable (2 TByte/4 TByte/6 TByte) KISS Stor 0/1 (2 TByte/4 TByte)
POWER SUPPLY	100-240 V AC (80+ gold)
EXPANSION SLOTS	1x PCIe x16 (16 Lanes, Gen 3), 1x PCIe x16 (4 Lanes, Gen 3), 1x PCIe x8 (1 Lane Gen 3), 1x PCIe x4 (4 Lanes, Gen 3), 1x PCIe x4 (1 Lane, Gen 3), 2x PCI (32 Bit, 33 MHz, Rev. 2.3)
EXPANSION CARDS*	GPUs: AMD FirePro W7100, Nvidia Quadro M4000 SSCs: PCIe SSDs up to 1.2 TByte ETH (RJ-45): 2x 1 Gbit/s, 4x 1 Gbit/s, 2x 10 Gbit/s Profibus: cIFX 70E-DP
CERTIFICATIONS	CE, designed for UL
ALTITUDE	3.000 m
SHOCK**, ACCORDING TO EN 60068-2-27	Operating: 15 G 11 ms duration
VIBRATION**, ACCORDING TO EN 60068-2-6	Operating: 10-150 Hz: 1G/3 axis
OPERATING TEMPERATURE	0 °C to +50 °C
STORAGE TEMPERATURE	-20 °C to +70 °C
HUMIDITY	10 % to 93 % @ 40 °C, non-condensing
MTBF	50.000 h*
SECURITY	Kontron APPROTECT
VERIFIED OS	Windows 7/10, Linux

*) depending on configuration
**) no HDD

▶ CORPORATE OFFICES

EUROPE, MIDDLE EAST & AFRICA

Lise-Meitner-Str. 3-5
86156 Augsburg
Germany
Tel.: + 49 821 4086 0
Fax: + 49 821 4086 111
info@kontron.com

NORTH AMERICA

14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: + 1 888 294 4558
Fax: + 1 858 677 0898
info@us.kontron.com

ASIA PACIFIC

1-2F, 10 Building, No. 8 Liangshuihe 2nd Street,
Economical & Technological Development Zone,
Beijing, 100176, P.R.China
Tel.: +86 10 63751188
Fax: +86 10 83682438
info@kontron.cn